

Ranpak void filling systems the natural choice



FillPak®

High-volume, high-speed void filling



FillPak offers high volume void filling with speed and cost efficiency

FillPak converts 76 cm, fanfold kraft paper into a PaperStar configuration for fast and efficient void filling.

Everything, from the PaperStar shape, to the height of the machine, to its speed and operation, has been designed to maximize throughput and minimize cost in a high-speed void fill operation.

Single-ply fanfold kraft paper allows the system to operate at extreme high speed, with virtually no ramp up time. The unique pack design allows 5 packs to be stacked and adhered together, enabling optimization of the time needed to pack the products and providing maximum throughput.

- **Adaptable:** easy to integrate into any packing area
- **High-volume:** designed exclusively for high volume users
- **High output:** converting speed of 1,4 m/s
- **Optimisation:** increases speed and efficiency of the packing process
- **User friendly:** easy to install and use
- **Environmentally friendly:** 100% biodegradable, recyclable and renewable



Packaging Engineering

Ranpak's Packaging Engineers are experts in the design, analysis and testing of in-the-box packaging. Send your packaging challenge to Ranpak and one of our Packaging Engineers will design a packaging solution that will ensure that your product arrives at your customer economically and damage-free. Ranpak's Packaging Engineers analyze your current packaging and benchmark this against its own packaging design recommendations.

Each package design report provides you with our recommended packaging solution and includes a thorough cost analysis and comparative test results. This way it is directly clear how much you can save on materials while realizing damage reductions. Ranpak's Packaging Engineers and Sales Representatives can visit your facility to train your packers on how to use our products and they can perform an on-site cost analysis.



Integrated Applications

Ranpak can increase your output by integrating our converters into your packaging lines. Our System Engineers can even design a custom converter to fit your unique situation and application for the most efficient, safe and user-friendly operation.

Specifications

Converter

Dimensions WxDxH*	90x97x235 cm
Weight	176 kg
Voltage	100-230 Volt
Power	200 Watt
Max current	2 Amp
Frequency	50/60 Hz
Operation	Manual, footswitch, EDS
Speed	0,8/1,2/1,4 m/s
Cut method	Electric motor
Accessories	Papercart, footswitch



Paper pack

Dimensions WxDxH*	76x19x23 cm
Basis weight	50 gr/m ²
Length	500 m
Weight	20 kg
Width	76 cm
Average yield	3 m ³



Paper pallet

Dimensions WxDxH*	120x80x110 cm
Weight	480 kg
Packs per pallet	24



* Width x Depth x Height

Your FillPak® distributor:



P.O. Box 139 / 6400 AC
Heerlen / The Netherlands
T +31 45 5470470
F +31 45 5426844
E info@ranpakeurope.com



This brochure is printed on:



Mixed Sources
Product group from well-managed
forests and other controlled sources
www.fsc.org Cert no. SCS-COC 001890
© 1996 Forest Stewardship Council