

# Ranpak void filling systems the natural choice



## FillPak TT<sup>®</sup> with Cut Mechanism

**Makes void filling  
with paper even easier**



**Gives FillPak TT the ability to cut  
and pre-define paper lengths**

FillPak TT with cut mechanism converts 38 cm, fanfold kraft paper into a PaperStar™ configuration, for fast and efficient void filling.

In addition to adding a cut mechanism to the FillPak TT, the upgrade also gives the operator the ability to pre-set paper lengths via Electronic Delivery System (EDS) mode. The unit can be set up to dispense void fill material in lengths of 30 cm up to 3 meters.

The TT with cut mechanism has the same small footprint as the regular FillPak TT and can be easily adapted to any packing environment or integrated into areas with limited space.

- **User friendly:** a very comfortable and ergonomic way of packing
- **EDS functionality:** work with pre-set paper lengths
- **High output:** converting speed of 1,4 m/s
- **Compact:** small, light and easy to use
- **Adaptable:** very suitable for areas with multiple packing stations
- **Environmentally friendly:** 100% biodegradable, recyclable and renewable



## Packaging Engineering

Ranpak's Packaging Engineers are experts in the design, analysis and testing of in-the-box packaging. Send your packaging challenge to Ranpak and one of our Packaging Engineers will design a packaging solution that will ensure that your product arrives at your customer economically and damage-free. Ranpak's Packaging Engineers analyze your current packaging and benchmark this against its own packaging design recommendations.

Each package design report provides you with our recommended packaging solution and includes a thorough cost analysis and comparative test results. This way it is directly clear how much you can save on materials while realizing damage reductions. Ranpak's Packaging Engineers and Sales Representatives can visit your facility to train your packers on how to use our products and they can perform an on-site cost analysis.

## Integrated Applications


Ranpak can increase your output by integrating our converters into your packaging lines. Our System Engineers can even design a custom converter to fit your unique situation and application for the most efficient, safe and user-friendly operation.



## Specifications


### Converter

Dimensions WxDxH*	43x57x33 cm (head)	
Weight	13 kg (head)	
Voltage	100-230 Volt	
Power	150 Watt	
Max. Current	1,6 Amp	
Frequency	50/60Hz	
Operation	Footswitch, EDS	
Speed	1,4 m/s (50gr) 1,2 m/s (70gr)	
Cut method	Electric motor	
Accessories	Footswitch	




### Stand

	Table clamp	Floor stand
Width	40 cm	108 cm
Depth	39 cm	108 cm
Height **	125-150 cm	188-213 cm
Weight ***	24,5 kg	30 kg



### Paper pack

Dimensions WxDxH*	38x19x23 cm	38x19x23 cm
Basis weight	50 gr/m <sup>2</sup>	70 gr/m <sup>2</sup>
Length	500 m	360 m
Weight	10 kg	10 kg
Width	38 cm	38 cm
Average yield	1,5 m <sup>3</sup>	1,5 m <sup>3</sup>



### Paper pallet

Dimensions WxDxH*	120x80x110 cm
Weight	480 kg
Packs per pallet	48

\* Width x Depth x Height

\*\* Min. / max. height dimensions are measured with the head at its max tilt

\*\*\* Includes the weight of the head

## Your FillPak TT® distributor:



P.O. Box 139 / 6400 AC  
Heerlen / The Netherlands  
T +31 45 5470470  
F +31 45 5426844  
E info@ranpakeurope.com



This brochure is printed on:

